Declaration of Performance

Nr.: 15651-0534-1-UK

1. Unique identification of product type:

EN 15651-1: F-INT-EXT CC EN 15651-4:2012 PW EXT-INT CC

2. Identification of construstion product:

PU Sealant Adhesive 534
Batch number: See product packaging

3. Intended use of product:

Sealant for use in facade elements

Type F-INT-EXT CC

Sealant for use in pedestrian walkways
Type PW-EXT-INT CC

4. Adress and name of the producer:

Dana Lim A/S, Københavnsvej 220, 4600 Køge, Danmark

5. Name and adress of authorized representative:

Not relevant

6. System and verification of consistency of the construction product (Annex V):

System 3 + 3

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:

The notified body Ift Rosenheim GmbH (0757)

performed the testing of reaction to fire under system 3 and issued a test report

8. In case of declaration of performance concerning a construction product covered by a European Technical Assessment has been issued:

Not relevant



Declared Performance: Conditioning: Method A

Substrate: Anodised aluminium (Without primer) and grout type M1 (Without primer)

| Essential characteristic | | Performance | Harmonized technical specification |
|-----------------------------------|--|-------------|------------------------------------|
| Reaction to fire | | E | |
| Release of chemicals dangerous to | | Evaluated | |
| health a | and environment | | |
| Water a | nd air thightness | | |
| a) | Resisistance to flow | ≤ 3 mm | |
| b) | Loss of volume | ≤ 10 % | |
| с) | Tensile properties at maintained extension after water immersion | NF | |
| d) | Tensile properties at maintained extension | NF | |
| e) | Tensile properties at maintained extension; - 30°C | NF | EN 15651-1:2012 EN 15651-4:2012 |
| f) | Adhesion/cohesion properties at maintained extension after 28 days water immersion | NF | |
| g) | Adhesion/cohesion properties at maintained extension after 28 days salt water immersion | NF | |
| h) | Tear resistance | NF | |
| i) | Durability | Pass | |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Køge, 10.06.2014

Erik Andersen Laboratoriechef

