



Product and Material Safety Information

Date of issue: 2022-12-20

Basic product data

Product identification: 100 % polymer-based extruded products

Product group: EPDM

Supplier information

Trelleborg Sealing Profiles Sweden AB

Box 1004, SE-331 29 Värnamo

Website: www.trelleborg.com

Contact: Customer support

Telephone +46 370 48100

E-mail: support.sealingprofiles@trelleborg.com

Trelleborg Sealing Profiles Sweden AB is a responsible company that works to contribute to sustainable development by integrating environmental and social concerns into our daily work. As part of our total quality management, we pay attention to environmental and health and safety impacts of our products and processes. We require the same level of commitment including full compliance with applicable legal requirements from all our business partners. We are a producer of articles and a downstream user of chemical substances. We will use our best effort to provide updated and relevant information required for compliance with the REACH and RoHS-regulation.

Trelleborg Sealing Profiles Sweden AB possesses certification in compliance with ISO 9001:2015, ISO 14001:2015 and IATF 16949:2016.

Hazards identification

Vulcanized rubber is an article and not subject to classification or requirements to provide Safety Data Sheets according to REACH 1907/2006/EG chapter 31.

First aid and Fire Fighting

Skin contact: Recommendation to wash hands after use

Flammable/toxic gases will form upon decomposition

Extinguish the fire by cooling with water spray

Storage and Disposal

Dark and cool (10-25°C ventilated area)

It is possible to recycle energy for all or parts of the product by combustion

Waste code for the supplied product is 17 09 04, alternatively depending on usage

Supplied product is not subject to classification as hazardous waste

Physical and Chemical properties

Physical form: Solid and/or cellular rubber

Colour: Black (white, brown or grey)

Odor: Typical rubber

Decomposition temperature > 250 °C

Density (g/cm³) 0, 25 - 1, 40

Toxicological Information

Inhalation: No hazard under 100 °C

Skin contact: No hazard at industrial handling of dry profiles. When handling of surface treatment profiles or profiles with bleeding materials it's recommended using protective gloves and washing hands before breaks and after work.

Eye contact: In case of eye contact flush eyes.

Inhalation: Do not inhale dust

The highly refined mineral oils and naphtha distillates in our products contain, according to IP 346, a DMSO extract of less than 3% (w/w) and according to Note L, Annex VI of Regulation EU 1272/2008 is not classified as carcinogenic.

Indoor environment

The product does not have any emissions